



CHECK VALVE

BRASS SWING CHECK VALVE, PN16

Model Number: MV30-1401

FEATURES / CHARACTERISTICS

Rating	PN16
Connection	BS EN 10226-1 BSPP Threaded(ex BS21)
Working Medium	Water, Oil and Steam.

Horizontal Swing Pattern, Threaded Cover
Suitable for mounting in Horizontal and Vertical pipe
(with vertical flow upwards)

ON REQUEST

NPT Threads(subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE

Shell- 24 bar
Seat- 17.6 bar

WORKING TEMPERATURE

16 Bar -10° C to 110° C water

MATERIAL SPECIFICATIONS

	PARTS	MATERIAL
1	Cap	Brass CW617N
2	Packing	PTFE
3	Hinge Pin	Brass CW617N
4	Hinge	H62
5	Disc	Brass CW617N
6	Hinge Nut	H62
7	Body	Brass CW617N

DIMENSIONS (mm)

Sizes		d	L	H
DN	inch			
15	½"	13	49	31.5
20	¾"	17	58	36
25	1"	23	69	43.5
32	1¼"	28	76	45.5
40	1½"	33	83	52
50	2"	44	92	57.5

*All dimensions are nominal (indicative)
Actual dimensions may vary

