

Model: **MV30-211W-300**

Check Valve

Resilient Seated Wafer Ends



FEATURES / CHARACTERISTICS

Design	API 594
Rating	300PSI
Connections	ASME B16.1 Class 125
Applications	Fire protection, potable water, etc.

Double door wafer style spring loaded check valve, Suitable for vertical or horizontal installation

ON REQUEST

Other Pressure Ratings (subject to minimum order quantities)

MAXIMUM OPERATING PRESSURE

300 PSI (20.6 bar)

WORKING TEMPERATURE

32°F to 180°F (0°C to 82°C)

MATERIAL SPECIFICATIONS

PARTS	MATERIAL	SPECIFICATION
Body	Ductile Iron	A536 65-45-12
Disc	Aluminum Bronze Stainless Steel Stainless Steel	B584 C95400 A351 CF8 A351 CF8M
Stem	Stainless Steel	AISI 304/AISI 316
Seat Ring	EPDM	Commerical
Spring	Stainless Steel	AISI 304/AISI 316

DIMENSIONS(mm)

SIZE		H
mm	inch	
50	2"	54
65	2½"	60
80	3"	67
100	4"	67
125	5"	83
150	6"	95
200	8"	127
250	10"	140
300	12"	181

*All dimensions are nominal (indicative)
Actual dimensions may vary

Note:

Lifting ring for DN200(8") and above

