



CHECK VALVE

BRASS FOOT CHECK VALVE, PN10

Model Number: MV30-4407

FEATURES / CHARACTERISTICS

Rating	PN10
Connection	BS EN 10226-1 BSPP Threaded(ex BS21)
Working Medium	Water, Oil and Steam.

Brass Body Lift Pattern Foot Valve,
Stainless Steel Mesh Threaded Ends

ON REQUEST

NPT Threads (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE

Shell- 15 bar

Seat- 11 bar

WORKING TEMPERATURE

10 Bar -10° C to 110° C water

MATERIAL SPECIFICATIONS

	PARTS	MATERIAL
1	Body	Brass CW617N
2	Bonnet	Brass CW617N
3	Disc	Brass CW617N
4	Stem	Brass CW617N
5	Rubber	Nitrile Rubber
6	Spring	Stainless Steel 304
7	Mesh	Stainless Steel 304

DIMENSIONS (mm)

DN	inch	L	H
15	1/2"	33	70
20	3/4"	41	80
25	1"	46	93
32	1 1/4"	56	98
40	1 1/2"	64	112
50	2"	81	137
65	2 1/2"	97	153
80	3"	111	177
100	4"	140	180

*All dimensions are nominal (indicative)
Actual dimensions may vary

