

GATE VALVE

BRONZE, RISING STEM, PN20 Model Number: MV40-1138.RS

FEATURES / CHARACTERSTICS

Design BS EN12288/B

(ex BS5154)

Rating PN20

Connection BS EN 10226-1

BSPP Threaded(ex BS21)

Working Medium Water, Oil and Steam.

Threaded Bonnet, Rising Stem

Single Piece Wedge

ON REQUEST

NPT Threads, (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE WORKING TEMPERATURE

Shell- 30 bar 20 Bar -10° C to 110° C water

Seat- 22 bar

MATERIAL SPECIFICATIONS

	PARTS	MATERIAL
1	Nut	Brass CW614N
2	ID Plate	Aluminium
3	Handwheel	Aluminium
4	Stem	DZR Brass CW602N
5	Packing	Brass CW614N
6	Stem Bush	DZR Brass CW602N
7	Packing	PTFE
8	Bonnet	Bronze CC491K
9	Body	Bronze CC491K
10	Disc	Bronze CC491K

DIMENSIONS (mm)

Siz	zes	L	Н	D
DN	inch			
15	1/2''	43	112	55
20	3/4''	49	125	63
25	1"	54	143	70
32	11/4"	62	170	70
40	1½"	65	198	80
50	2"	75	233	90

^{*}All dimensions are nominal (indicative) Actual dimensions may vary



