

Model: **MV40-1211FF-250**

Gate Valve

Resilient Seated OS&Y Type-Flanged Ends



FEATURES / CHARACTERISTICS

Design	AWWA C515/BS5163
Rating	250PSI
Connections	ANSI B16.1 Class 125
Applications	Fire protection, potable water, etc.

OS&Y Type, Resilient Wedge, Fusion bonded coating comply with AWWA C550

ON REQUEST

Other Pressure Ratings (subject to minimum order quantities)

MAXIMUM OPERATING PRESSURE

250 PSI (17.2 bar)

WORKING TEMPERATURE

32°F to 180°F (0°C to 82°C)

MATERIAL SPECIFICATIONS

PARTS	MATERIAL	SPECIFICATION
Body	Ductile Iron	A536 65-45-12
Wedge	Ductile Iron EPDM Coated	
Wedge Nut	Stainless Steel	AISI 304
Stem	Stainless Steel	AISI 304/420
Bonnet	Ductile Iron	A536 65-45-12
Gasket	EPDM	Commercial
Packing	Graphite/PTFE	Non- asbestos
Stem Nut	Bronze	ASTM B62
Handwheel	Ductile Iron	A536 65-45-12

DIMENSIONS(mm)

SIZE		L	H	D
mm	inch			
350	14"	381	1577	508
400	16"	406	1800	558
450	18"	432	2048	610

*All dimensions are nominal (indicative)
Actual dimensions may vary

