

Gate Valve

Resilient Seated OS&Y Type-MJ-MJ Ends



FEATURES / CHARACTERISTICS

Design	AWWA C515/BS5163
Rating	300PSI
Connections	AWWA C 153
Applications	Fire protection, potable water, etc.

OS&Y Type, Resilient Wedge, Fusion bonded coating comply with AWWA C550

ON REQUEST

Other Pressure Ratings (subject to minimum order quantities)

MAXIMUM OPERATING PRESSURE

300 PSI (20.6 bar)

WORKING TEMPERATURE

32°F to 180°F (0°C to 82°C)



MATERIAL SPECIFICATIONS

PARTS	MATERIAL	SPECIFICATION
Body	Ductile Iron	A536 65-45-12
Wedge	Ductile Iron EPDM Coated	
Wedge Nut	Stainless Steel	AISI 304
Stem	Stainless Steel	AISI 304/420
Bonnet	Ductile Iron	A536 65-45-12
Gasket	EPDM	Commercial
Packing	Graphite/PTFE	Non- asbestos
Stem Nut	Bronze	ASTM B62
Handwheel	Ductile Iron	A536 65-45-12

DIMENSIONS(mm)

SIZE		L	H	D
mm	inch			
80	3"	241	462	253
100	4"	254	514	253
150	6"	292	709	306
200	8"	318	922	355
250	10"	375	1116	445
300	12"	378	1300	445

*All dimensions are nominal (indicative)
Actual dimensions may vary

