



#### FEATURES / CHARACTERISTICS

Design	AWWA C515/BS5163
Rating	200PSI
Connections	ANSI B16.1 Class 125
Applications	Fire protection, potable water, etc.

Bolted Bonnet, Non-Rising Stem, Resilient Wedge,  
Epoxy Coated Interior/Exterior, Flanged Ends

#### ON REQUEST

Other Pressure Ratings (subject to minimum order quantities)

#### MAXIMUM OPERATING PRESSURE

200 PSI (13.7 bar)

#### WORKING TEMPERATURE

32°F to 180°F (0°C to 82°C)



#### MATERIAL SPECIFICATIONS

PARTS	MATERIAL	SPECIFICATION
Body	Ductile Iron	A536 65-45-12
Wedge Disc	Ductile Iron EPDM Coated	
Disc Nut	Bronze	ASTM B62
Stem	Stainless Steel	AISI 304/420
Gasket	EPDM	Commercial
Bonnet	Ductile Iron	A536 65-45-12
Thrust Collar	Bronze	ASTM C51100
Gland	Ductile Iron	A536 65-45-12
Wrench Nut	Ductile Iron	A536 65-45-12
Post Plate	Ductile Iron	A536 65-45-12

#### DIMENSIONS(mm)

SIZE		L	H	D
mm	inch			
500	20"	457	1142	305
600	24"	508	1295	305

\*All dimensions are nominal (indicative)  
Actual dimensions may vary

