



STRAINER

BRONZE Y-STRAINER, PN20
Model Number: MV70-116



FEATURES / CHARACTERISTICS

Rating PN20
 Connections BS EN 10226-2
 Taper Threaded (ex BS21)
 Working Medium Water, Oil and Steam

Stainless Steel Screen,
 Screwed Cap

ON REQUEST

NPT Threads, (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE

Shell- 30 bar

WORKING TEMPERATURE

20 Bar -10° C to 110° C water
 WRAS approved -10° C to 85° C

MATERIAL SPECIFICATIONS

SR.	PARTS	MATERIAL
1	Body	Bronze CC491K
2	Screen	Stainless Steel 304
3	Gasket	Bronze CC491K
4	Cap	PTFE
5	Plate	Aluminum

DIMENSIONS (mm)

Sizes		L	H	Diameter of Hole	Meshes /cm ²
DN	inch				
15	½"	58	40	0.7	60
20	¾"	70	51	0.7	60
25	1"	88	58	0.7	60
32	1¼"	96	69	1.4	28
40	1½"	107	74	1.4	28
50	2"	126	95	1.4	28

*All dimensions are nominal (indicative)
 Actual dimensions may vary

