

STRAINER

BRASS Y-STRAINER, PN16 Model Number: MV70-1604



FEATURES / CHARACTERSTICS

Rating PN16

Connections BS EN 10226-2

Taper Threaded (ex BS21)

Working Medium Water, Oil and Steam

Stainless Steel Screen, Screwed Cap

ON REQUEST

NPT Threads, (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE

WORKING TEMPERATURE

Shell- 24 bar 16 Bar -10° C to 110° C water



| MATERIAL SPECIFICATIONS | | | | |
|-------------------------|--------|--------------|--|--|
| SR. | PARTS | MATERIAL | | |
| 1 | Body | Brass CW617N | | |
| 2 | Cap | Brass CW617N | | |
| 3 | Gasket | PTFE | | |
| 4 | Screen | SS304 | | |

DIMENSIONS (mm)

| Sizes | | | | Meshes |
|-------|--------|-----|----|--------|
| DN | inch | L | Н | /cm² |
| 15 | 1/2" | 54 | 33 | 120 |
| 20 | 3/4'' | 63 | 36 | 60 |
| 25 | 1" | 73 | 42 | 28 |
| 32 | 11/4'' | 89 | 51 | 28 |
| 40 | 1½" | 95 | 52 | 28 |
| 50 | 2" | 113 | 72 | 16 |

^{*}All dimensions are nominal (indicative) Actual dimensions may vary



