



# STRAINER

**DZR Y-STRAINER, PN20**

**Model Number: MV70-604**



## FEATURES / CHARACTERISTICS

Rating PN20  
Connections BS EN 10226-2  
Taper Threaded (ex BS21)  
Working Medium Water, Oil and Steam

Stainless Steel Screen,  
Screwed Cap

## ON REQUEST

NPT Threads, (subject to minimum order quantities)

## HYDROSTATIC TEST PRESSURE

Shell- 30 bar

## WORKING TEMPERATURE

20 Bar -10° C to 110° C water

## MATERIAL SPECIFICATIONS

SR.	PARTS	MATERIAL
1	Valve Body	DZR(CZ132A)
2	Bonnet	DZR(CZ132A)
3	Strainer	Stainless Steel
4	Gasket	PTFE
5	Nameplate	Steel (L2)
6	Rivet	Stainless Steel

## DIMENSIONS (mm)

Sizes		L	H	B	E	Threads	Meshes /cm <sup>2</sup>
DN	inch						
15	½"	57	34.5	15	11.5	5.3	30
20	¾"	72	39.5	18.5	14	6.5	30
25	1"	74.5	43	21	16	5.9	30
32	1¼"	95	54	29	18	6.5	20
40	1½"	105	61.5	32	18	6.5	20
50	2"	129	74.5	46	21	8.0	20

\*All dimensions are nominal (indicative)  
Actual dimensions may vary

