

HOSE BIB COCK

DZR BIB-COCK WITH HOSE UNION, PN16

Model Number: MV700-2D

FEATURES / CHARACTERSTICS

Rating PN16 Connection ISO228 Working Medium Water

Nickel Plated DZR Body, Chrome Plated Brass Ball, Quarter Turn Dacromet plated Lever, Hose Connection

ON REQUEST

NPT Threads (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE


Shell- 17.6 bar

WORKING TEMPERATURE

16 Bar -10° C to 110° C water

MATERIAL SPECIFICATIONS

	PARTS	MATERIAL			
1	Body	DZR (Ni Plated)			
2	Ball	Brass C38000 (Cr. Plated)			
3	Seat	PTFE			
4	Bonnet	DZR (Ni Plated)			
5	Stem	Brass C38000 (Ni. Plated)			
6	O-Ring	NBR			
7	Handle	Carbon Steel (DAC Plated)			
8	Screw	Stainless Steel			
9	Washer Ring	NBR			
10	Union Nut	Brass C38000 (Ni. Plated)			
11	Hose Pipe	Stainless Steel			
12	Mainfold	PP			



DIMENSIONS (mm)

Sizes						_	_	
DN	inch	Α	В	С	D	E	F	G
15	1/2''	83	52	37	46.5	G¾''	G½"	10
20	3/4''	83	58	52	49	G1"	G¾''	12

^{*}All dimensions are nominal (indicative) Actual dimensions may vary