



GLOBE VALVE

CAST IRON, RISING STEM PN16

Model Number: **MV50-1211**

FEATURES / CHARACTERISTICS

Design	BS EN 13789 (ex BS5152)
Rating	PN16
Connection	Flanged BS EN1092-2 (ex BS 4504, PN16)
Working Medium	Water, Oil, Steam

Outside Screwed Yoke, Epoxy Coated
Rising Stem.

ON REQUEST

ANSI standards (subject to minimum order quantities).

HYDROSTATIC TEST PRESSURE

Shell- 24 bar
Seat- 17.6 bar

WORKING TEMPERATURE

16 Bar -10° C to 100° C water

MATERIAL SPECIFICATIONS

	PARTS	MATERIAL
1	Body	Cast Iron
2	Disc	Ductile Iron
3	Body Seat Ring	Bronze
4	Disc Seat Ring	Bronze
5	Bonnet	Cast Iron
6	Stem	Stainless Steel
7	Gland Packing	Graphite

DIMENSIONS (mm)

Sizes		L	H	D
DN	inch			
65	2 ½"	216	336	190
80	3"	241	345	190
100	4"	292	389	305
125	5"	330	425	305
150	6"	356	511	305
200	8"	495	580	455
250	10"	622	720	455
300	12"	698	859	455

*All dimensions are nominal (indicative)
Actual dimensions may vary

